

ANSI H.S.S. CHUCKING REAMER SET

STRAIGHT SHANK, STRAIGHT FLUTE, RIGHT-HAND CUT

ISO9001



5500-SX00



5500-SB00



5500-SE00



5500-SK00

Features:

- H.S.S.
- Straight shank, ANSI standard
- Straight flute, right-hand cut
- Diameter tolerance: +0.0001" to +0.0005"
-0.0000"

Item	Piece per Set	Range	Price
5500-SF00	29	Fractional Sizes — 1/16" thru 1/2" by 64ths	\$336.00/SET
5500-SL00	26	Letter Sizes — A thru Z	\$336.00/SET
5500-SX00	14	Over & Under Sizes — 0.1240" thru 0.5010"	\$186.00/SET
5500-SB00	25	Metric Sizes — 1.0mm thru 13.0mm by 0.5mm	\$325.00/SET
5500-SK00	60	Wire Gauge Sizes — #1 thru #60 in a Strong USA HUOT Metal Box	\$718.00/SET
5500-SE00	13	Fractional Sizes — 1/16" thru 1/4" by 64ths Jobber length	\$189.00/SET

5500-SF00, in a Wooden Box
29pcs/set: 1/16" thru 1/2" by 64ths

Size	Dec. Equiv.	Flute Legth	Overall Length
1/16"	0.0625"	1/2"	2-1/2"
5/64"	0.0781"	3/4"	3"
3/32"	0.0938"	3/4"	3"
7/64"	0.1094"	7/8"	3-1/2"
1/8"	0.1250"	7/8"	3-1/2"
9/64"	0.1406"	1"	4"
5/32"	0.1562"	1"	4"
11/64"	0.1719"	1-1/8"	4-1/2"
3/16"	0.1875"	1-1/8"	4-1/2"
13/64"	0.2031"	1-1/4"	5"
7/32"	0.2188"	1-1/4"	5"
15/64"	0.2344"	1-1/2"	6"
1/4"	0.2500"	1-1/2"	6"
17/64"	0.2656"	1-1/2"	6"
9/32"	0.2812"	1-1/2"	6"
19/64"	0.2969"	1-1/2"	6"
5/16"	0.3125"	1-1/2"	6"
21/64"	0.3281"	1-1/2"	6"
11/32"	0.3438"	1-1/2"	6"
23/64"	0.3594"	1-3/4"	7"
3/8"	0.3750"	1-3/4"	7"
25/64"	0.3906"	1-3/4"	7"
13/32"	0.4062"	1-3/4"	7"
27/64"	0.4219"	1-3/4"	7"
7/16"	0.4375"	1-3/4"	7"
29/64"	0.4531"	1-3/4"	7"
15/32"	0.4688"	1-3/4"	7"
31/64"	0.4844"	2"	8"
1/2"	0.5000"	2"	8"

5500-SL00, in a Wooden Box
26pcs/set: A thru Z

Size	Dec. Equiv.	Flute Legth	Overall Length
A	0.2340"	1-1/2"	6"
B	0.2380"	1-1/2"	6"
C	0.2420"	1-1/2"	6"
D	0.2460"	1-1/2"	6"
E	0.2500"	1-1/2"	6"
F	0.2570"	1-1/2"	6"
G	0.2610"	1-1/2"	6"
H	0.2660"	1-1/2"	6"
I	0.2720"	1-1/2"	6"
J	0.2770"	1-1/2"	6"
K	0.2810"	1-1/2"	6"
L	0.2900"	1-1/2"	6"
M	0.2950"	1-1/2"	6"
N	0.3020"	1-1/2"	6"
O	0.3160"	1-1/2"	6"
P	0.3230"	1-1/2"	6"
Q	0.3320"	1-1/2"	6"
R	0.3390"	1-1/2"	6"
S	0.3480"	1-3/4"	7"
T	0.3580"	1-3/4"	7"
U	0.3680"	1-3/4"	7"
V	0.3770"	1-3/4"	7"
W	0.3860"	1-3/4"	7"
X	0.3970"	1-3/4"	7"
Y	0.4040"	1-3/4"	7"
Z	0.4130"	1-3/4"	7"



5500-SF00



5500-SL00