

RAZORWELD

RAZOR MULTI 210



MIG
GAS & GASLESS



TIG
DC LIFT ARC



STICK



3 YEAR
PRODUCT
WARRANTY



**SYNERGIC
PROGRAMS**



**FOOT PEDAL
READY**



**POWER FACTOR
CORRECTION**



**SPOOL GUN
READY**

A portable powerhouse, the **RAZOR MULTI 210** is built for any task in the workshop and on the worksite. Featuring intelligent MIG synergic control and 3-in-1 multiprocessing, the new **RAZOR MULTI 210** tackles MIG, TIG & STICK projects with power and efficiency.

TECHNICAL DATA

SKU	JRW210di
PRIMARY INPUT VOLTAGE	115/230V
SUPPLY PLUG	6-50 NEMA
IEFF (A)	16
RATED OUTPUT	25% @ 210A
PROTECTION CLASS	IP21S
INSULATION CLASS	B
MINIMUM GENERATOR (kVA)	11
DINSE CONNECTOR	35/50
STANDARD	CSA/CAN
WELDS	MILD STEEL, STAINLESS STEEL, CAST IRON, SILICON BRONZE, ALUMINUM, COPPER
WARRANTY (YEARS)	3

SIZE & WEIGHT

DIMENSIONS (inch)	22" x 8.6" x 16"
WEIGHT (pound)	37 lbs (Machine Only)

MIG SPECIFICATIONS

MIG WELDING CURRENT RANGE	30 - 210A
MIG DUTY CYCLE	25% @ 210A, 60% @ 136A, 100% @ 105A
MIG WIRE SIZE RANGE	0.023 - 0.040
MIG WIRE SPOOL SIZE	11 Pound
MIG WELDING THICKNESS RANGE	1/32" - 5/16"
DRIVE ROLLER SIZE	30/10

TIG SPECIFICATIONS

TIG FUNCTION TYPE	DC Lift Arc
TIG WELDING CURRENT RANGE	5 - 210A
TIG DUTY CYCLE @ 105F	25% @ 210A, 60% @ 136A, 100% @ 105A
TIG WELDING THICKNESS RANGE	1/32" - 5/16"

STICK SPECIFICATIONS

STICK WELDING CURRENT RANGE	20 - 180A
STICK DUTY CYCLE @ 105F	25% @ 180A, 60% @ 116A, 100% @ 90A
STICK ELECTRODE RANGE	1/16" - 5/32"
STICK WELDING THICKNESS RANGE	1/16" - 3/8"



JASIC TECHNOLOGIES AMERICA INC
25503 74TH AVE S KENT WA 98032
WWW.RAZORWELD.COM